

## 256—Fuel

Fuel shall be of a commercial type generally distributed by road service stations, except in cases of special waivers granted by the A.C.N.s with the consent of the C.S.I. in favour of promoters of events taking place in countries where the quality of commercial fuel is insufficient.

Upper-cylinder or two-stroke engine lubricants are authorised, on condition they do not increase the fuel octane number.

## CHAPTER II—Group 1: Series Production Touring Cars

### 257—Definition

Series production Touring cars are motor vehicles intended for the transportation of persons and for which the manufacturer has endeavoured to obtain the best performance in normal conditions of use.

In order to enjoy recognition in the "Touring" category, these cars must be in conformity with a model well defined in a catalogue and obviously intended for normal use, "for pleasures or business." They must be offered to customers by the regular sales department of their manufacturer.

They must be of a model in current production or which has not been definitely abandoned for over four years. They must have been manufactured in series at a minimum rate of 1,000 units in 12 consecutive months and be identical as far as mechanism and coach work are concerned.

By identical is meant that the external shape and the component materials of the mechanical parts, the chassis and the body must remain unchanged.

To the exception of the modifications and additions explicitly authorised according to the present regulations any accessory and/or any mechanical part may only be replaced by the same accessory or the same part used by the manufacturer for the considered model, the only tolerances in size being those officially foreseen by the factory.

All elements of the vehicle must compulsorily be those of one same recognised model, whether said model is the basic one or one of its variants also recognised (see art. 254) to the exception of elements whereof the addition, the removal or the replacement is explicitly authorized according to the regulations hereafter.

### 258—Coachwork

Series production touring cars shall have a closed body or a "convertible" body.

Coachwork means all the external parts of the vehicle licked by the air streams and located above a plane passing through the wheel hubs.

Convertible coachwork means a body which can be either completely closed, or open, with inter alia mobile windows in the doors. Is excluded all coachwork fitted with a simple hood offering but a scanty protection against bad weather, even if the hood is equipped with detachable side-screens.

As a rule the body shall be built by the manufacturer of the chassis. However, a series production body manufactured by a coachwork builder