

exceed the limits specified for the group concerned, may pass into a higher group, provided for in the supplementary regulations, with the prescription of which it complies and under the following conditions:

- Group 1 passes into group 2.
- Group 3 passes into group 4.
- Group 4 (or 3+4) passes into group 5.
- Group 5 (or 3+4+5) passes into group 6.

TITLE III

SERIES PRODUCTION TOURING CARS (Group 1)

Art. 255.—Definition: touring cars built on large series production terms. These cars shall compete in an event without having undergone any preparation likely to improve their performances or their conditions of use. The only working authorized is normal maintenance or the replacement parts damaged through wear or accident and the modifications and additions explicitly authorized hereafter under article 257. Except for what is explicitly authorized any part damaged through wear or accident may only be replaced by an original part which must be exactly the same as the one for which it is substituted.

Art. 256.—Minimum production and number of seats: series-production touring cars shall have been manufactured in a quantity of at least 5,000 identical units and offer at least 4 seats, except if their engine cylinder-capacity is inferior or equal to 700 cc. In which case the manufacturer may deliver them as two-seaters.

Art. 257.—Mountings and modifications authorized:

a) **Lighting devices:** all lighting and signalling devices must comply with the legal requirements of the country of the event; cars from abroad must comply in this respect with the Convention on international road traffic.

Lighting devices which are part of the standard equipment must remain those foreseen by the manufacturer and must comply as far as is concerned their functioning with what the manufacturer has foreseen for the considered model. Thus, if changing from a road beam to a passing beam is produced by merely deflecting the beam inside one same reflector, this system may not be altered.

Freedom is granted with regard to the frontal glass, the reflector and the bulbs.

The mounting of additional headlights is authorized provided that a total of 6 headlights is not exceeded (parking lights not included). Extra headlights may, if necessary, be fitted into the front part of the coachwork or into the radiator grille, but such openings as needed in this case must be completely filled by the additional headlights. Shall be considered as a headlight any lighting-device throwing a beam towards the front (dipped-beam, long range lamp, anti-fog lamp).

The fitting of reverse-lights is authorized, if necessary by embedding into the coachwork, but provided it will only switch on when engaging the reverse-gear, and provided the police regulations are respected.

The mounting of manoeuvrable search-lights on the roof or elsewhere is forbidden.

Waivers may be granted to these specifications on condition that they be explicitly provided for in the supplementary regulations of the event.

To comply with legal requirements of certain countries, it is permissible to rearrange the casing of front signalling devices in order to house both traffic indicators and parking lights.